


Frontline

Heavy Contract Matting Tile in an attractive linear design, incorporating scraper fibres.




Robust

Heavy Contract Ribbed Tile, perfect for entrances and circulation areas.











Checkpoint

Prestige velour matting tile with excellent absorption properties, incorporating scraper fibres.



All colours are for illustrative purposes only.
If colour choice is critical, please request a sample.

Technical Specification

	FRONTLINE	CHECKPOINT	ROBUST
 Tile Size	500 x 500mm	500 x 500mm	500 x 500mm
 Pile Weight	740g/m ²	830g/m ²	1,150g/m ²
 Total Weight	4700g/m ²	3910g/m ²	4,400g/m ²
 Total Thickness	7.2mm	8.2mm	9.5mm
Construction			
Pile Type	100% PA6 Aqualon HD	100% Polyamide	100% Polypropylene
Backing	Bitumen backed	Bitumen backed	Bitumen backed
Technical Data			
 Fire Rating	ISO 13501-1 Bfl-S1	ISO 1350101 Bfl-S1	EN 13297 Efl
 Wear Rating	BS EN 1307 Class 33-LC2	BS EN 1307 Pass	For heavy wear areas
 Rubbing Fastness	ISO 105 x 12 ≥ 4	ISO 105 x 12 - Pass	
 Walk on Test	BS ISO 6356 ≤ 2kV		Permanent anti-static

Easy Installation

Ensure the subfloor is smooth, hard, dry and clean and that a damp proof membrane has been incorporated if required. Install using appropriate carpet tile tackifier. For a copy of our installation guide please contact our sales office.

Easy Maintenance

Regular vacuuming is essential to avoid build-up of soil. Periodic professional cleaning is recommended. For a copy of our Maintenance Guide please contact our sales office.

