surestep® original R10

Surestep Original offers a fresh alternative to conventional safety flooring with an improved cleaner aesthetic. A palette of 30 colours combines gradations of hue and lightness.

Specifications: R10, ESf, TRRL ≥36, Rz ≥20

**Speckled weld also available.*


Surestep Original **171842** | pistachio

171532 | sun LRV 49
171462 | brick LRV 16
171562 | pepper LRV 10
172382 | cappuccino LRV 28
171132 | bianco LRV 69
171812 | taupe LRV 22
172492 | orange LRV 32
171512 | oyster LRV 49
171602 | plum LRV 9
172022 | lavender LRV 29
171222 | dune* LRV 47
171332 | violet LRV 39
171082 | snow* LRV 75
171362 | clay* LRV 47
171842 | pistachio LRV 35
171442 | jade LRV 30
172262 | grass LRV 31
171732 | storm* LRV 22
171032 | smoke* LRV 47
171422 | trout* LRV 53
171302 | pale LRV 48
171712 | sky LRV 35
172142 | turquoise LRV 32
171962 | steel* LRV 11
171992 | charcoal* LRV 6
171282 | dragon LRV 10
171262 | umber* LRV 19
171952 | elephant* LRV 19
171642 | cloudy LRV 21
171782 | night LRV 7

Description		Sheet safety vinyl
Dimensions		Roll width 2m Roll length 20-27 lm
Total thickness	ISO 1765	2.0mm
Thickness wear layer	EN-ISO 24340	0.7mm
Collection size		30
Application	EN 10874	Class 34/43
Slip resistance	EN 13845 Annex C	ESf
	DIN 51130	R10
	TRRL Pendulum – Wet test – slider 96	≥ 36
CE	EN 14041	
Reaction to fire	EN 13501-1	B_{fl}-s1
Slip resistance	EN 13893	DS: ≥0.30

surestep® star R10

Innovative, muted and sophisticated. The 13 contemporary tones offer hints of grey and a unique aesthetic. Surestep Star offers a brighter visual with holographic particles colour matched to the terazzo or natural base colour of each item.

Specifications: R10, ESf, TRRL ≥36, Rz ≥20



Surestep Star **176082** | snow + **176072** | pewter

Description		Sheet safety vinyl
Dimensions		Roll width 2m Roll length 20-27 lm
Total thickness	ISO 1765	2.0mm
Thickness wear layer	EN-ISO 24340	0.7mm
Collection size		13
Application	EN 10874	Class 34/43
Slip resistance	EN 13845 Annex C	ESf
	DIN 51130	R10
	TRRL Pendulum – Wet test – slider 96	≥ 36
CE	EN 14041	
Reaction to fire	EN 13501-1	B_{fl}-s1
Slip resistance	EN 13893	DS: ≥0.30

176362 | clay LRV 49
176262 | umber LRV 19
176412 | forest LRV 22
176692 | mouse LRV 28
176072 | pewter LRV 25
176922 | concrete LRV 28
176032 | smoke LRV 47
176422 | trout LRV 54
176082 | snow LRV 75
176272 | raisin LRV 15
176952 | mercury LRV 14
176982 | carbon LRV 8
176282 | dragon LRV 11

BREEAM generic ratings
Step safety flooring – PVC Floor Covering with enhanced slip resistance (EN13845)

Building Type Office	Education	Healthcare	Multi Residential	Retail (Durability)	Retail (Fashion)	Meets Ska criteria
A	A+	A+	B	A	A+	✔

Our recommended adhesive is 540 Eurosafe Special or 640 Eurostar Special.
Full technical specifications are available at www.forbo-flooring.co.uk/downloads
Please note: Digital representations may vary from the actual product.
Please order a sample to see the full effect. Contact 0800 731 2369.