POLYFLOR™
COVERING THE WORLD

Polysafe™ Quattro PUR

BAREFOOT & SHOD, WET & DRY.


SAFETY FLOORING




Chalk Dune **5766** w/r 5766
NCS S 1502-Y50R LRV 60




Lunar Shell **5772** ▲ w/r 5772
NCS S 1502-Y LRV 64




Barley Cove **5761** ▲ w/r 5212
NCS S 3005-Y50R LRV 47




Truffle Shore **5762** ▲ w/r 5762
NCS S 5005-Y50R LRV 24




Sea Spray **5763** ▲ w/r 5202
NCS S 3000-N LRV 49



Sea Mist **5768** w/r 5205
NCS S 2010-B LRV 46



Calm Azure **5770** w/r 5206
NCS S 2030-R90B LRV 31




Deep Lagoon **5771** w/r 5207
NCS S 6010-R90B LRV 12




HSE Compliant
50+
Pendulum Wet Test


Sustainable Slip Resistance
throughout product's guaranteed life




Cool Pebble **5767** w/r 2090
NCS S 3000-N LRV 46



Slate Haze **5773** w/r 5764
NCS S 5000-N LRV 26



Coastal Flint **5764** ▲ w/r 5764
NCS S 4500-N LRV 26



Granite Sky **5765** ▲ w/r 4490
NCS S 7502-B LRV 10

w/r = weld rod **NCS** = Natural Colour System **LRV** = Light Reflectance Value
▲ = These colours contain a tonal chipped decoration

P4 AS 4586

POLYSAFE PUR OPTIMUM APPEARANCE

A+ BRE GENERIC ENVIRONMENTAL RATING
Refer to BRE Global ratings on www.greenbooklive.com

100% RECYCLABLE
CONTAINS RECYCLED MATERIAL