POLYFLOR™
COVERING THE WORLD

Polysafe™ Standard PUR

SAFETY FLOORING



Elmwood **4520** w/r 9610
NCS S 3010-Y60R LRV 38.8

Ash Grey **4540** w/r 2090
NCS S 3502-B LRV 36.9



Cool Aqua **4570** w/r 4570
NCS S 3020-B10G LRV 34.9



Storm Blue **4560** w/r 4910
NCS S 5020-R80B LRV 15.3

Autumn Beige **4140** w/r 4140
NCS S 3010-Y30R LRV 38.9



Silver Birch **4020*** w/r 9200
NCS S 4500-N LRV 26.7



Cedar Blue **4060*** w/r 9040
NCS S 5030-B LRV 13.9



Lilac Blue **4580** w/r 4580
NCS S 4020-R60B LRV 22.8



Maple Fawn **4030*** w/r 4030
NCS S 4020-Y50R LRV 27.3



Alpine Green **4110** w/r 4110
NCS S 4010-G30Y LRV 27.1



Arctic Blue **4130** w/r 4130
NCS S 4020-B LRV 25.2



Nordic Grey **4090** w/r 8680
NCS S 5005-B20G LRV 23.6



Antique Copper **4120** w/r 4120
NCS S 4040-Y80R LRV 17.8

Redwood **4040*** w/r 9230
NCS S 3060-Y90R LRV 12.1



Twilight **4490** w/r 4490
NCS S 7502-B LRV 9.8

Black Walnut **4150** w/r 8640
NCS S 8505-Y20R LRV 6.3

w/r = weld rod **NCS** = Natural Colour System **LRV** = Light Reflectance Value

All colours are available in 2.0mm and 2.5mm gauge. ***Available in 3.5mm gauge**

100% RECYCLABLE
CONTAINS RECYCLED MATERIAL

A+ BRE° ENP 472 ENVIRONMENTAL RATING

POLYSAFE PUR OPTIMUM APPEARANCE

36+ **Sustainable Slip Resistance** throughout product's guaranteed life
RRL Pendulum Wet Test - HSE Compliant

° Refer to BRE Global ratings on www.greenbooklive.com