

sarlon® wood XL modern 15 & 19 dB

Sarlon Wood XL Modern and Sarlon Oak offer a natural elegant wood appearance, coupled with a 15 dB or 19 dB impact sound reduction.



		LRV 15
15 dB 423422 / 19 dB 438422 carbon		LRV 15
15 dB 423420 / 19 dB 438420 clay		LRV 23
15 dB 423430 / 19 dB 438430 chalk		LRV 47

sarlon® oak 15 & 19 dB



Description	Sheet acoustic vinyl
Dimensions	ISO 2441 Roll width 2,0m Roll width 2,5m
Total thickness	ISO 2440 15 dB 2,6mm 19 dB 3,4mm
Thickness wear layer	EN-ISO 24340 15 dB 0,7mm 19 dB 0,67mm
Collection size	Varies by design
Application	ISO 10254/EN635 Class 34/42
Impact sound reduction	EN-ISO 717-2 ΔLw = 15 dB ΔLw = 19 dB
Indoor impact noise	EN 5 31-024 Level < 65 dB Class A
Residual indentation	EN-ISO 24431 15 dB -0,05mm 19 dB -0,05mm
Requirement	≤ 0,20mm

CE	EN 14041
Reaction to fire	EN 13501-1 C-s1
Slip resistance	EN 13893 DS-30/30

Our recommended adhesive is SdE Eurosafe Special or SdE Eurosafe Special Full technical specifications are available at www.sarlon-flooring.co.uk/downloads. Please note Digital representations may vary from the actual product. Please order a sample to see the full effect. Contact 0800 731 7269.

sarlon® concrete 15 & 19 dB

		LRV 13
15 dB 432734 timber / 19 dB 433734		LRV 13
		LRV 16
15 dB 432742 pewter / 19 dB 433742		LRV 12
15 dB 432761 steel / 19 dB 433761		LRV 16
15 dB 432771 silver / 19 dB 433771		LRV 29
15 dB 432713 pearl / 19 dB 433713		LRV 28

sarlon® linea 15 & 19 dB

Sarlon Linea and Sarlon Zebrano are contemporary designs with a modern wood-like appearance.



		LRV 28
15 dB 423113 / 19 dB 433113 sand		LRV 28
15 dB 423121 / 19 dB 433121 light grey		LRV 36
15 dB 423132 / 19 dB 433132 charcoal		LRV 17

sarlon® zebrano 15 & 19 dB



		LRV 44
15 dB 423311 / 19 dB 433311 light grey		LRV 44
15 dB 423319 / 19 dB 433319 charcoal		LRV 12
15 dB 423313 / 19 dB 433313 sand		LRV 38