

Expona Flow PUR

HARDWEARING COMMERCIAL SHEET VINYL FLOORCOVERING, INCLUDING STYLISH WOOD AND EFFECT DESIGNS



 Luna 9844 W19184 NCS 5 90-9	 Oatmeal 9840 W19180 NCS 5 20-9	 Flaxen 9849 W19184 NCS 5 90-9	 Burnt Orange 9848 W19184 NCS 5 30-10
 Storm 9845 W19185 NCS 5 30-9	 Moleskin 9841 W19181 NCS 5 20-9	 Meadow 9850 W19180 NCS 5 30-9	 Plum 9847 W19187 NCS 5 40-10
 Jet 9842 W19182 NCS 5 80-10	 Taupe 9843 W19183 NCS 5 70-10	 Teal 9851 W19181 NCS 5 40-10	 Mulberry 9846 W19186 NCS 5 40-10
 Steel Blue 9852 W19182 NCS 5 60-10	 Midnight 9854 W19184 NCS 5 10-10	 Woodland 9853 W19183 NCS 5 40-10	


KEY FEATURES

Heterogeneous commercial vinyl sheet floorcovering.  
Authentic wood and contemporary effect designs, in a choice of 50 shades.  
Polyurethane reinforcement, to facilitate a low-cost, polish-free maintenance regime.  
Conforms to EN 649 / EN ISO 10582.










\* Refer to BRE Global ratings on [www.greenbooklive.com](http://www.greenbooklive.com)

 Light Grey Concrete 9858 W19188 NCS 5 30-10	 Warm Concrete 9855 W19185 NCS 5 30-10	
 Cool Concrete 9856 W19186 NCS 5 40-10	 Dark Grey Concrete 9857 W19187 NCS 5 60-10	
 Light Industrial Concrete 9860 W19180 NCS 5 20-10	 Dark Industrial Concrete 9859 W19189 NCS 5 40-10	
 Copper Ornamental 9861 W19181 NCS 5 10-10	 Onyx Ornamental 9862 W19182 NCS 5 70-10	

The  shown denote a ramp test result, which is an ex-factory measure of slip resistance.  
For safety flooring with sustainable wet slip resistance, refer to Expona Control PUR or the PolySafe ranges.

SPECIFICATIONS

        
GAUGE: 2.0mm, wear layer 0.7mm  
AVAILABILITY: Sheet: 2m x 20m



This product is a highly realistic replication of natural materials. Hence, on many designs, natural variations in texture and colour will be present.

Please note: due to limitations of colour printing, actual samples should be seen before colour selection is made.